

RFT – 847

4 * DVB-S/S2 --> IP STREAMER



RFT-847 transforms digital 8PSK/QPSK programs from four satellite TV transponder to IP transport stream. Then satellite TV programs can be received with PC, IP STB or Smart TV.

RFT-847 is valid for SD and HD programs.

With one RFT-847 unit can be transmitted 4 *TS (up to 50 programs) as unicast or up to 8 programs as multicast.

RFT-847 can be equipped with CI slot (option) for the most common CA modules.

Assembly for RFT-800 system or stand-alone.

Easy WEB control interface.

Features

- Satellite TV programs with Smart TV
- SD and HD
- 4 transponders as unicast or up to 8 programs as multicast

Technical specification

8PSK/QPSK demodulator

- Frequency range 950-2150 MHz
- Input level -65 ... -25 dBm
- Automatic FEC selection
- DVB-S/S2 compatible

IP output

- SPTS
- Max. Bit rate 40 Mbit/s
- Unicast and Multicast UDP streaming
- UpnP-DNLA 1.5 Server
- IGMP Server
- Support SAP (Service Announcement Protocol)

General

- Power consumption 16VDC/1,1A
- Input 2* F-female
- Output 1* RJ-45
- Dimensions 71 mm*214 mm* 149 mm

