

RFT – 897HD

HDMI --> IP STREAMER



RFT-897HD is a HD encoder to modulate HDMI signal to IP transport stream.

Maximum resolution of HDMI input is 1920*1080i.

Adjustable bit rate 1,5 ... 9 Mbps.

RFT-897HD is perfect in Hotel IPTV system to transmit information from PC/HDMI to IPTV as well as to transmit the prestations of conference room to public facilities in HD quality.

HD encoder can be used also in theaters and concert halls.

Encoder is easy to install and program.

Available models:	RFT-897HD-1	1 program
	RFT-897HD-2	2 programs
	RFT-897HD-3	3 programs

Features

- HD
- HDMI input
- IP output

Technical specification

Video encoder

- MPEG-4 H.264 AVC
- MPEG-2 ISO-13818
- Adjustable bit rate
1,5 - 9 Mbps
- Max. resolution
1920*1080i, 720p

Audio encoder

- AAC
- Compliant to ISO/IEC11172-3
- Max bit rate 256 kbps

IP output

- SPTS
- Max. Bit rate 100 Mbit/s
- Unicast and Multicast UDP, RTP streaming

General

- Power consumption
16VDC/1,1A
- Output 1* RJ-45
- Dimensions 71 mm*214 mm*
149 mm

RF-Tuote Oy, Joensuunkatu 13, 24100 Salo, FINLAND
tel: +358-2-7366360, fax: +358-2-7366355
e-mail: info@rf-tuote.fi www.rf-tuote.fi

