

MK-400 serien

4 MUX DVB-S/S2/S2X/T/T2 --> QAM/COFDM/DVB-T2
UHDTV RE/CROSS MODULATOR



MK-400 transforms digital programs from 4 independent DVB-S/S2/S2X/T/T2/C inputs to 1...4QAM or COFDM outputs. After that process satellite TV programs can be received with DVB-C or DVB-T TV or STB.

MK-400 features possibility to make own DVB multiplex.

Easy web based programming and remote configuration is possible.

Output frequency range from 114 MHz to 1006 Mhz.

Channel memory numbering LCN (Logical Channel Number) can be saved by manual and by channel to channel.

Automatic/manual NIT.

Separate PID filtering possibility.

Can be assembled to 19" rack or direct to wall mounting
CA-modules can be used in all incoming muxes so called flexcam support.

6 CA-module slots.

Possible to remote control via Smartportal service by mobile phone , pad or PC world widely.

Models:

MK-400	4*DVB-S/S2,-T/T2,-C IN, 1...4 QAM/COFDM OUT
MK-480	4*DVB-S/S2,-T/T2,-C IN, 1...8 QAM/COFDM OUT
MK-420	4*DVB-S/S2,-T/T2,-C IN, 1...4 DVB-T2 OUT
MK-406CI	4*DVB-S/S2,-T/T2,-C IN, 1...4 QAM/COFDM OUT 6*CI
MK-486CI	4*DVB-S/S2,-T/T2,-C IN, 1...8 QAM/COFDM OUT 6*CI
MK-426CI	4*DVB-S/S2,-T/T2,-C IN, 1...4 DVB-T2 OUT 6*CI



Features

- Satellite TV programs with DVB-C or-T TV or STB
- 4 independent DVB-S/S2/S2X/T/T2/C inputs, 1...4(8) QAM/COFDM output

- Remux/Cross mux options

- 4k UHDTV , HD ja SD

Technical specification

Demodulators

- Frequency range 48-2150 MHz
- Input level -65 ... -25 dBm
- Automatic FEC selection
- DVB-S/S2/S2X/T/T2/C compatible

QAM/COFDM output

- Constellation 32, 64, (C:128, 256 QAM)
- MER > 40dB
- Output level 100 dBuV max
- Output frequency range 114 ... 1006 MHz

Universal:

- Power consumption 100-240 VAC/ 50W
- Dimensions: 41*270*480mm

