

IPM-20

20 TV-CHANNELS HTTP/HLS STREAMS FROM
INTERNET --> DVB-C/T HD/UHD MODULATOR



IPM-20 is a HD/UHD modulator for max to 20 internet TV HSL streaming or internetvideo broadcasting on DVB-C or -T format to coaxial network.

Resolution and compression are forwarded from input signal as original thought the device process. Max resolution is 4k UHD. Supports EPG adding.

To modulation format can be selected cable DVB-C or terrestrial DVB-T.

Unit is very easy to set up without any extra control unit , by a web browser.

It is possible to connect Axing Smartportal.
Redundant power supply as option (RPS).

Available models:

20chs: IPM-20 and IPM-20RPS



Features

- SD, HD, 4k UHD
- IPTV input:
8*RJ-45/1Gbps
UDP, HLS, SRT
UDP Multicast
- DVB-C/T output

Technical parameters

Output

- 1 Female F-connector
- DVB-C
QAM64,QAM128,QAM256
- Baud rate 5 to 6,96MS/s
- 2k, 8k @ DVB-T / QAM64
- Output level 100 dBuV max
- Output frequency range:
114 ... 950 MHz
- NIT + LCN
- Program name
- EGP

General

- Power consumption
100-240 VAC/ 70W
- Size: 1RU 19" rack

